

Date of compilation: 19.12.2017

Date of revision: - - -

# Version: 1



# According to 1907/2006/EC (REACH), 2015/830/EU **GELCOAT FILLER STYRENE FREE**

Safety data sheet

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: GELCOAT FILLER STYRENE FREE

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Car repair

Uses advised against: All uses not specified in this section or in section 7.3

1.3 **Details of the supplier of the safety data sheet:** 

> Troton Sp. z o.o. Zabrowo 14A

78-120 Goscino - Zachodniopomorskie - Polska

Phone .: +48 94 35 123 94 -Fax: +48 94 35 126 22 troton@troton.com.pl www.troton.pl

1.4 **Emergency telephone number:** (8am-4pm)+48 094 35 123 94; 112

# **SECTION 2: HAZARDS IDENTIFICATION**

#### Classification of the substance or mixture: 2.1

#### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Lig. 3: Flammable liquids, Category 3, H226 Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1: Sensitisation, skin, Category 1, H317

#### 2.2 **Label elements:**

#### CLP Regulation (EC) No 1272/2008:





# **Hazard statements:**

Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 3: H226 - Flammable liquid and vapour Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

# **Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of water

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P403+P235: Store in a well-ventilated place. Keep cool

P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively

#### Substances that contribute to the classification

Methyl methacrylate

#### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Non-applicable





#### **GELCOAT FILLER STYRENE FREE**

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

#### 3.2 Mixture:

Chemical description: Polyester resin

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification			
CAS: 25013-15-4	Vinyltoluene 1	Self-classified		
EC: 246-562-2 Index: Non-applicable REACH 01-2119622074-50-	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Danger	10 - <25 %	
CAS: 80-62-6	Methyl methacrylate	ATP CLP00		
EC: 201-297-1 Index: 607-035-00-6 REACH 01-2119452498-28-	Regulation 1272/2008	Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	1 - <10 %	
CAS: 123-31-9	Hydroquinone 1	ATP ATP01		
EC: 204-617-8 Index: 604-005-00-4 REACH 01-2119524016-51-	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Carc. 2: H351; Eye Dam. 1: H318; Muta. 2: H341; Skin Sens. 1: H317 - Danger	<1 %	

<sup>&</sup>lt;sup>1</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

# **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

# By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

# 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

# SECTION 5: FIREFIGHTING MEASURES

# 5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

# 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.





#### **GELCOAT FILLER STYRENE FREE**

### SECTION 5: FIREFIGHTING MEASURES (continued)

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

#### **6.1** Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

#### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

#### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

### **SECTION 7: HANDLING AND STORAGE**

# 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

#### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 35 °C

Maximum time: 12 Months

B.- General conditions for storage





# **GELCOAT FILLER STYRENE FREE**

# SECTION 7: HANDLING AND STORAGE (continued)

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

# 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	Environmental limits		
Methyl methacrylate	IOELV (8h)	50 ppm	
CAS: 80-62-6	IOELV (STEL)	100 ppm	
EC: 201-297-1	Year	2017	

#### **DNEL (Workers):**

		Short e	xposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Vinyltoluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 25013-15-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 246-562-2	Inhalation	Non-applicable	Non-applicable	37 mg/m³	37 mg/m <sup>3</sup>
Methyl methacrylate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 80-62-6	Dermal	Non-applicable	Non-applicable	13,67 mg/kg	Non-applicable
EC: 201-297-1	Inhalation	Non-applicable	Non-applicable	208 mg/m <sup>3</sup>	208 mg/m <sup>3</sup>
Hydroquinone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-31-9	Dermal	Non-applicable	Non-applicable	128 mg/kg	Non-applicable
EC: 204-617-8	Inhalation	Non-applicable	Non-applicable	7 mg/m³	1 mg/m³

# **DNEL (General population):**

		Short e	xposure	Long ex	posure
Identification		Systemic	Local	Systemic	Local
Methyl methacrylate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 80-62-6	Dermal	Non-applicable	Non-applicable	8,2 mg/kg	Non-applicable
EC: 201-297-1	Inhalation	Non-applicable	Non-applicable	74,3 mg/m <sup>3</sup>	104 mg/m <sup>3</sup>
Hydroquinone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-31-9	Dermal	Non-applicable	Non-applicable	64 mg/kg	Non-applicable
EC: 204-617-8	Inhalation	Non-applicable	Non-applicable	1,74 mg/m³	0,5 mg/m <sup>3</sup>

# PNEC:

Identification				
Vinyltoluene	STP	1 mg/L	Fresh water	0,0498 mg/L
CAS: 25013-15-4	Soil	0,133 mg/kg	Marine water	0,002 mg/L
EC: 246-562-2	Intermittent	0,013 mg/L	Sediment (Fresh water)	0,684 mg/kg
	Oral	2,5 g/kg	Sediment (Marine water)	0,0684 mg/kg
Methyl methacrylate	STP	10 mg/L	Fresh water	0,94 mg/L
CAS: 80-62-6	Soil	1,47 mg/kg	Marine water	0,94 mg/L
EC: 201-297-1	Intermittent	0,94 mg/L	Sediment (Fresh water)	5,74 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
Hydroquinone	STP	0,71 mg/L	Fresh water	0,000114 mg/L
CAS: 123-31-9	Soil	0,000129 mg/kg	Marine water	0,0000114 mg/L
EC: 204-617-8	Intermittent	0,00134 mg/L	Sediment (Fresh water)	0,00098 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,000097 mg/kg

# 8.2 Exposure controls:

A.- General security and hygiene measures in the work place





#### **GELCOAT FILLER STYRENE FREE**

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

#### C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420 and EN 374.

<sup>&</sup>quot;As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

#### D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

#### E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing	CAT III	EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2001 EN ISO 14116:2015 EN 1149-5:2008	Limited protection against flames.
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	CAT III	EN 13287:2008 EN ISO 20345:2011	Replace boots at any sign of deterioration.

### F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2002	Eyewash stations	DIN 12 899 ISO 3864-1:2002

#### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties:

\*Not relevant due to the nature of the product, not providing information property of its hazards.





# **GELCOAT FILLER STYRENE FREE**

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid
Appearance: Viscous

Colour: According to the markings on the package

Odour: Characteristic
Odour threshold: Non-applicable \*

Volatility:

Boiling point at atmospheric pressure: 157 °C Vapour pressure at 20 °C: 620 Pa

Vapour pressure at 50 °C: 2960 Pa (3 kPa) Evaporation rate at 20 °C: Non-applicable \*

**Product description:** 

Density at 20 °C: 1350 kg/m<sup>3</sup> Relative density at 20 °C: Non-applicable \* Dynamic viscosity at 20 °C: Non-applicable \* Kinematic viscosity at 20 °C: Non-applicable \* Kinematic viscosity at 40 °C: >20,5 cSt Concentration: Non-applicable \* pH: Non-applicable \* Vapour density at 20 °C: Non-applicable \* Partition coefficient n-octanol/water 20 °C: Non-applicable \* Solubility in water at 20 °C: Non-applicable \* Solubility properties: Non-applicable \* Non-applicable \* Decomposition temperature: Melting point/freezing point: Non-applicable \* Non-applicable \* Explosive properties: Oxidising properties: Non-applicable \*

Flammability:

Flash Point: 46 °C

Flammability (solid, gas): Non-applicable \*

Autoignition temperature: 421 °C
Lower flammability limit: Not available
Upper flammability limit: Not available

Explosive:

Lower explosive limit: Non-applicable \*
Upper explosive limit: Non-applicable \*

9.2 Other information:

Surface tension at 20 °C:

Refraction index:

Non-applicable \*

Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.





#### **GELCOAT FILLER STYRENE FREE**

# SECTION 10: STABILITY AND REACTIVITY (continued)

### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

# SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A.- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
  - Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - · Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:





# **GELCOAT FILLER STYRENE FREE**

# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

#### H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

#### Other information:

Non-applicable

# Specific toxicology information on the substances:

Identification Acute toxic		cute toxicity	Genus
Vinyltoluene	LD50 oral	5100 mg/kg	Rat
CAS: 25013-15-4	LD50 dermal	>2000 mg/kg	
EC: 246-562-2	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Methyl methacrylate	LD50 oral	>2000 mg/kg	
CAS: 80-62-6	LD50 dermal	>2000 mg/kg	
EC: 201-297-1	LC50 inhalation	>20 mg/L (4 h)	
Hydroquinone	LD50 oral	450 mg/kg	Rat
CAS: 123-31-9	LD50 dermal	>2000 mg/kg	
EC: 204-617-8	LC50 inhalation	>5 mg/L	

#### SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

# 12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
Vinyltoluene	LC50	7.6 mg/L (96 h)	Salmo gairdneri	Fish
CAS: 25013-15-4	EC50 1.3 mg/L (48 h) Daphnia magna		Crustacean	
EC: 246-562-2	EC50 2.6 mg/L (72 h) Selenastrum capricornutum		Algae	
Methyl methacrylate	LC50	191 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 80-62-6	EC50	69 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-297-1	EC50	170 mg/L (96 h)	Selenastrum capricornutum	Algae
Hydroquinone	LC50	0.1 - 1 mg/L (96 h)		Fish
CAS: 123-31-9	EC50	0.1 - 1 mg/L		Crustacean
EC: 204-617-8	EC50	0.1 - 1 mg/L		Algae

# 12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Methyl methacrylate	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 80-62-6	COD	Non-applicable	Period	14 days
EC: 201-297-1	BOD5/COD	Non-applicable	% Biodegradable	94,3 %

# 12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential		
Vinyltoluene	BCF	5	
CAS: 25013-15-4	Pow Log	3.44	
EC: 246-562-2	Potential	Low	
Methyl methacrylate	BCF	7	
CAS: 80-62-6	Pow Log	1.38	
EC: 201-297-1	Potential	Low	

# 12.4 Mobility in soil:





#### **GELCOAT FILLER STYRENE FREE**

# SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
Vinyltoluene	Koc	Non-applicable	Henry	Non-applicable
CAS: 25013-15-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 246-562-2	Surface tension	3,2E-2 N/m (20 °C)	Moist soil	Non-applicable
Methyl methacrylate	Koc	Non-applicable	Henry	Non-applicable
CAS: 80-62-6	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 201-297-1	Surface tension	2,551E-2 N/m (25 °C)	Moist soil	Non-applicable
Hydroquinone	Koc	Non-applicable	Henry	Non-applicable
CAS: 123-31-9	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-617-8	Surface tension	6,35E-3 N/m (360,18 °C)	Moist soil	Non-applicable

#### 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

#### 12.6 Other adverse effects:

Not described

#### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
	It is not possible to assign a specific code, as it depends on the intended use by the user	Dangerous

### Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP4 Irritant — skin irritation and eye damage

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

# SECTION 14: TRANSPORT INFORMATION

#### Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:



**14.1 UN number:** UN3269

14.2 UN proper shipping name: POLYESTER RESIN KIT

**14.3** Transport hazard class(es): 3

Labels: 3
14.4 Packing group: III
14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 236, 340
Tunnel restriction code: E

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Transport in bulk according to Non-applicable

Annex II of Marpol and the

IBC Code:

Transport of dangerous goods by sea:





#### **GELCOAT FILLER STYRENE FREE**

# SECTION 14: TRANSPORT INFORMATION (continued)

With regard to IMDG 38-16:

**14.1 UN number:** UN3269

**14.2 UN proper shipping name:** POLYESTER RESIN KIT

**14.3 Transport hazard class(es):** 3 labels: 3

14.4 Packing group: III
14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 236, 340
EmS Codes: F-E, S-D
Physico-Chemical properties: see section 9
Limited quantities: 5 L

14.7 Transport in bulk according to Non-applicable

Annex II of Marpol and the

IBC Code:

#### Transport of dangerous goods by air:

With regard to IATA/ICAO 2017:



**14.1 UN number:** UN3269

14.2 UN proper shipping name: POLYESTER RESIN KIT

14.3 Transport hazard class(es): 3
Labels: 3

14.4Packing group:III14.5Environmental hazards:No

14.6 Special precautions for user

Physico-Chemical properties: see section 9 **14.7 Transport in bulk according to** Non-applicable

Annex II of Marpol and the

**IBC Code:** 

# SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Non-applicable

# Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

# Other legislation:

The product could be affected by sectorial legislation

### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

# SECTION 16: OTHER INFORMATION

# Legislation related to safety data sheets:





#### **GELCOAT FILLER STYRENE FREE**

#### SECTION 16: OTHER INFORMATION (continued)

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

#### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

#### Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation

H317: May cause an allergic skin reaction H226: Flammable liquid and vapour H319: Causes serious eye irritation

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed Acute Tox. 4: H332 - Harmful if inhaled

Aquatic Acute 1: H400 - Very toxic to aquatic life

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Carc. 2: H351 - Suspected of causing cancer Eye Dam. 1: H318 - Causes serious eye damage Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 2: H225 - Highly flammable liquid and vapour Flam. Liq. 3: H226 - Flammable liquid and vapour Muta. 2: H341 - Suspected of causing genetic defects

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction STOT SE 3: H335 - May cause respiratory irritation

#### Classification procedure:

Skin Irrit. 2: Calculation method Skin Sens. 1: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

### Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

#### **Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol—water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.