

Printing date 09.11.2016 Version number 3 Revision: 25.01.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name PUR PF 150-15N A-Komp
- · Utilization of the substance of the formulation: polyurethane resin
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application for the substance / the preparation polyurethane resin
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Vosschemie Benelux byba

- · Mechelsesteenweg 303
- · B-2500 Lier
- · Tel: +32 (0)3 489 28 28
- · Fax: +32 (0)3 488 19 27
- · mailto: info@vosschemie-benelux.com
- · Further information obtainable from: environment protection department
- · 1.4 Emergency telephone number:

During normal opening times (7 am - 5 pm)

phone: +32 (0)70 245 245

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Acute Tox. 4

H332 Harmful if inhaled.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07

GHS09

- · Signal word Warning
- · Hazard statements

H332 Harmful if inhaled.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 2)

(Contd. of page 1)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.11.2016 Version number 3 Revision: 25.01.2016

Trade name PUR PF 150-15N A-Komp

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Resin mixture

· Dangerous components:		
CAS: 38640-62-9	alkylated aromatic hydrocarbon	25 - 50%
EINECS: 254-052-6	♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 1, H410	
Reg.nr.: 01-2119565150-48		
CAS: 110-63-4	butane-1,4-diol	1.0-2.5%
EINECS: 203-786-5	♠ Acute Tox. 4, H302; STOT SE 3, H336	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Personal protection for the First Aider.

Immediately remove any clothing soiled by the product.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Aspiration may cause pulmonary edema and pneumonitis.

A person vomiting while laying on their back should be turned onto their side.

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

Seek immediate medical advice.

- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

carbon dioxide

Nitrogen oxides (NOx)

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 3)



Printing date 09.11.2016 Version number 3 Revision: 25.01.2016

Trade name PUR PF 150-15N A-Komp

(Contd. of page 2)

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Inform personnel of the affiliated with the product hazards and risks

Store in cool, dry place in tightly closed receptacles.

provide for best ventilation in the work space

· Information about fire - and explosion protection:

Protect from heat.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

Keep container tightly closed and dry and storage in a good ventilated room.

Storage temperature: 15 - 25 °C.

· Information about storage in one common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

Store away from water.

Do not store together with oxidising and acidic materials as well as heavy-metal compounds.

· Further information about storage conditions:

Protect from heat and direct sunlight.

Store in dry conditions.

Protect from frost.

Protect from humidity and water.

- · Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)



Printing date 09.11.2016 Version number 3 Revision: 25.01.2016

Trade name PUR PF 150-15N A-Komp

(Contd. of page 3)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:		
110-63-4 butane-1,4-diol		
AGW (Germany)	Long-term value: 200 mg/m³, 50 ppm	
	4(II);AGS, 11	
MAK (Austria)	Short-term value: 800 mg/m³, 200 ppm	
	Long-term value: 200 mg/m³. 50 ppm	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Protection of hands:

Preventive skin protection (3-point program) required

Gloves approved to relevant standards as EN 374 (Europe) and F739 (U.S.)

tested gloves are used. Suitability and durability of a Glove is dependent on usage, for example frequency and duration of contact,

chemical resistance of glove material and dexterity Always seek advice from glove suppliers.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Natural rubber, NR

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Whitish

Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 5)



Printing date 09.11.2016 Version number 3 Revision: 25.01.2016

Trade name PUR PF 150-15N A-Komp

Undetermined. 100 °C 100 °C Not applicable. 190 °C Not determined. Product is not selfigniting. Product does not present an explosion hazard.
Not applicable. 190 °C Not determined. Product is not selfigniting.
90 °C Not determined. Product is not selfigniting.
Not determined. Product is not selfigniting.
Product is not selfigniting.
Product does not present an explosion hazard.
Not determined. Not determined.
Not determined.
9.98 g/cm³ Not determined. Not determined. Not determined.
nsoluble.
lot determined.
000 mPas Not determined.
0.3 % 0.3 g/l
V. V

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Violent reaction with concentrated alkali and oxidising agents.

No dangerous reactions known.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

water, alcohol, amine, base and acid

Incompatible with oxidizing agents, acids

· 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

(Contd. on page 6)



Printing date 09.11.2016 Version number 3 Revision: 25.01.2016

Trade name PUR PF 150-15N A-Komp

 (Contd. of page 5)

 • LD/LC50 values relevant for classification:

 38640-62-9 alkylated aromatic hydrocarbon

 Oral
 LD50
 > 4000 mg/kg (Ratte)

 NOAEL
 ~170 mg/kg (Ratte)

 Dermal
 LD50
 > 4000 mg/kg (Ratte)

 Inhalative
 LC50/4 h
 > 5.6 mg/l (Ratte)

- · Primary irritant effect:
- · Skin corrosion/irritation slightly irritant (OECD method), labelling not required
- · Serious eye damage/irritation

sligthly irritant, labelling not required

(analogy conclusion)

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxic	· Aquatic toxicity:		
38640-62-9 a	alkylated aromatic hydrocarbon		
LC0(96h)	0.5 mg/l (fish)		
EC0 (48h)	0.16 mg/l (D)		
LL50 (48h)	1.7 mg/L (D)		
EC0 (72h)	0.15 mg/l (A)		
NOEC (21d)	$0.013 \mu\text{g/l} (D)$		

- · 12.2 Persistence and degradability No further relevant information available.
- · Other information: Elimination by adsorption onto activated sludge
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- $\cdot \ \textbf{12.6 Other adverse effects} \ \textit{No further relevant information available}.$

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)



Printing date 09.11.2016 Version number 3 Revision: 25.01.2016

Trade name PUR PF 150-15N A-Komp

Must be specially treated adhering to official regulations.

(Contd. of page 6)

- · Uncleaned packaging:
- · Recommendation:

The empty containers may not be disposed of unless the adhesive to the container walls Been removed.

Disposal according to official regulations

14.1 UN-Number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANC
IMDG	LIQUID, N.O.S. (alkylated aromatic hydrocarbon) ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (alkylated aromatic hydrocarbo Naphtha (petroleum), hydrotreated heavy; naphtha,
IATA	low boiling point), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (alkylated aromatic hydrocarbon)
14.3 Transport hazard class(es)	
ADR	
Class Label	9 (M6) Miscellaneous dangerous substances and articles 9
IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances and articles.
	<u> </u>
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substance alkylated aromatic hydrocarbon
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances a articles.
Danger code (Kemler):	90
EMS Number:	F- A , S - F
Stowage Category	A

(Contd. on page 8)



Printing date 09.11.2016 Version number 3 Revision: 25.01.2016

Trade name PUR PF 150-15N A-Komp

	(Contd. of page
· Transport/Additional information:	Not dangerous according to the above specifications.
\cdot ADR	
· Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	E
\cdot IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU
G	SUBSTANCE, LIQUID, N.O.S. (ALKYLATED AROMATI
	HYDROCARBON), 9, III

SECTION 15: Regulatory information

- $\cdot 15.1\ Safety,\ health\ and\ environmental\ regulations/legislation\ specific\ for\ the\ substance\ or\ mixture$
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07 GHS09

- · Signal word Warning
- · Hazard statements

H332 Harmful if inhaled.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E1 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Waterhazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 09.11.2016 Version number 3 Revision: 25.01.2016

Trade name

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

· Department issuing SDS: environment protection department

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

GB ·